

## TECHNICAL DATA SHEET



IAP

### Inno Adhesion Promoter

*Accelerates the curing of Mega Bond PU and Mega Bond PU Speed.*

Inno Adhesion Promoter is a primer with solvents. It serves as an adhesive agent for the pre-treatment of plastics basing on PP/EPDM, SMC, PC, PA, ABS and PUR.



## TECHNICAL DATA

Appearance: Aerosol  
Colour: transparent/colourless  
Density: 0.86 kg/L (+/- 0,04, at 20°C (liquid stage)  
Propellant: G.P.L. (propane / butane)  
Flammability: Extremely flammable

## USER INSTRUCTIONS

- Not suitable for pure PE and PS.
- Shake can well before use.
- The surfaces to be coated must be free of oil, grease, wax, humidity, dirt, separating and caring agents.
- Apply a thin, even layer approximately 25 cm from the surface of the plastic. Leave to dry. An additional application is recommended.
- Can be over-lacquered with all current lacquer systems.

## APPLICATION

- After sanding (granulation: 120) and removing dust, spray the plastic primer thinly onto the plastic surface.
- Allow approx. 10 to 15 min. for evaporation.
- After a short drying period, a second coating layer is recommended.
- Also suitable as a primer for InnoBOND to increase adhesion to different surfaces/materials.

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product or their application. MS Ireland makes no warranties as to the accuracy of completeness of the information, and disclaims any liability regarding its use. MS Irelands only obligations are those in the standard terms and conditions of Sale for this product, and in no case will MS Ireland be liable for any Incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product.